

## TOURWAY



SPECIFICATION	PATTERN	PR	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OUTER DIAMETER	SECTION WIDTH	INFLATED PRESSURE		MAX LOAD	
									Single	Dual	Single	Dual
145R12C	TOURWAY	8	4.00B	TL	86/84	Q	537	145	450	450	530	500

## MILEWAY



SPECIFICATION	PATTERN	PR	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OUTER DIAMETER	SECTION WIDTH	INFLATED PRESSURE		MAX LOAD	
									Single	Dual	Single	Dual
155R12LT	MILEWAY	8	4.50B	TL	88/86	N	553	157	450	450	560	530

## ENERGYWAY III



SPECIFICATION	PATTERN	PR	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OUTER DIAMETER	SECTION WIDTH	INFLATED PRESSURE		MAX LOAD	
									Single	Dual	Single	Dual
185R14LT	ENERGYWAY III	8	51/2J	TL	102/100	Q	652	189	450	450	850	800
195R14LT	ENERGYWAY III	8	51/2J	TL	105/103	Q	668	196	450	450	925	875
195R15LT	ENERGYWAY III	8	51/2J	TL	106/104	Q	693	196	450	450	950	900

## ECOWAY I



SPECIFICATION	PATTERN	PR	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OUTER DIAMETER	SECTION WIDTH	INFLATED PRESSURE		MAX LOAD	
									Single	Dual	Single	Dual
7.00R16LT	ECOWAY I	12	5.50F	TL	115/110	L	783	200	670	670	1215	1060
7.50R16LT	ECOWAY I	14	5.50F	TL	118/114	L	783	200	770	770	1320	1180

## SMARTWAY I



SPECIFICATION	PATTERN	PR	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OUTER DIAMETER	SECTION WIDTH	INFLATED PRESSURE		MAX LOAD	
									Single	Dual	Single	Dual
5.00R12	SMARTWAY I	10	4.00B	TL	83/81	P	620	160	420	420	560	500

## SMARTWAY II



SPECIFICATION	PATTERN	PR	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OUTER DIAMETER	SECTION WIDTH	INFLATED PRESSURE		MAX LOAD	
									Single	Dual	Single	Dual
5.50R13LT	SMARTWAY II	8	4.00B	TL	88/84	P	620	160	420	420	560	500